

Canvas FF 5452

Fabric Spec Sheet



Date: 08/04/2026

Product Type: Sunbrella®

Use (Indoor / Outdoor): Residential / Commercial

Fabric Content	100% Sunbrella® Acrylic
Approx. Weight	7.8 oz per square yard / 12.4 oz per linear yard / 264.47 grams per square meter
Usable Width	54"
Finish	Non-PFAS Water & Stain Repellent
Weave Type	Plain
Backcoating	None / 0%
Repeat	Across the Roll (Warp): N/A Up the Roll (Fill): N/A
Railroaded - Yes/No	No
Reversible - Yes/No	No
Roll Size	60 Yards
Harmonized Code	5512.29.0000
Average Yarn Number	15.04
Cleaning Code	WS, BC
Warranty	5 years
Abrasion (Wyzenbeek)	ASTM D4157; Cotton Duck Abradant 45000 cycles
Pill Rating	ASTM 3511; Grade 1-5 5
Seam Slippage	ASTM D4034 Warp: 52 lbs. Fill: 45 lbs.
Break Strength	ASTM D5034 Warp: 300 lbs. Fill: 160 lbs.
Tear Strength	ASTM D2261 Warp: 18 lbs. Fill: 15 lbs.
Crocking	AATCC 8; Grade 1-5 Wet: 5 Dry: 5
Colorfastness to Light	AATCC 169-2003 Option 3: Grade 4 @ 2200 kjs
Flammability	Meets CA #117-2013 Sec. E (CS-191-53) Classification: 1 Normal Flammability *THIS FABRIC DOES NOT MEET ASTM E84 FOR PANELS OR NFPA 701 FOR DRAPERY UFAC Interior Fabrics Test Method-1990 - Meets Class I Requirements Complies with U.S. CPSC requirements for upholstered furniture flammability (16 CFR Part 1640)



Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention. ACT studies indicate that results of multiple abrasion tests performed on some fabric structures may vary significantly.

Learn more at: <http://sunbrella.com/abrasion>

Sunbrella® is a registered trademark of Glen Raven, Inc.